

TECHNICKÁ SPECIFIKACE

název	šířka	výška	rozteč		hloubka		výkon při top. spádu			váha	objem	koeficient	doporuče- ný výkon el.tyče
			připojení		od zdi vč. radiátoru (G) mm	od zdi k přívodu (g) mm	55/45 20°C	75/65 20°C	90/70 20°C				
			klasické (hD) mm	středové (h) mm			W	W	W				
OMEGA R	400	686	350	50	88-102	63-77	144	273	342	4,6	2,70	1,243	300
		915					185	349	438	6,1	3,60	1,2483	300
		1173					230	437	549	8,2	4,50	1,2563	400
		1402					272	516	648	9,8	5,40	1,2519	600
		1574					306	578	726	10,5	6,20	1,2485	600
		1746					340	642	806	12,2	6,80	1,2452	600
	500	686	450	50	103-117	77-87	175	330	413	5,5	3,20	1,24	300
		915					224	423	531	7,2	4,10	1,2437	400
		1173					278	529	665	9,7	5,20	1,256	600
		1402					331	626	786	11,6	6,30	1,2484	600
		1574					371	700	878	13,0	7,10	1,2427	600
		1746					413	777	974	14,4	7,90	1,237	900
	600	686	550	50	107-120	80-90	205	386	484	6,3	3,60	1,2373	400
		915					263	495	620	8,2	4,60	1,239	400
		1173					325	618	777	11,1	6,00	1,2556	600
		1402					387	731	918	13,3	7,20	1,2449	900
		1574					435	819	1026	14,9	8,10	1,2369	900
		1746					485	909	1137	16,5	9,10	1,2289	900
	700	1173	650	50	108-122	83-93	372	706	888	12,6	6,70	1,2553	600
		1402					443	835	1047	15,0	8,10	1,2415	900
		1574					499	935	1170	16,8	9,10	1,2311	900
		1746					556	1037	1295	18,7	10,20	1,2207	900
	800	915	750	50	110-124	85-95	337	632	791	10,4	5,70	1,2297	600
		1173					417	792	995	14,0	7,40	1,255	900
		1402					497	936	1173	16,7	9,00	1,238	900
		1574					561	1049	1311	18,8	10,10	1,2253	900
		1746					626	1163	1451	20,8	11,30	1,2125	1200